



Plan View
Scale - 1" = 25ft

SCHEDULE

Symbol	Label	Quantity	Manufacturer	Catalog Number	Description	Light Loss Factor	Wattage
	SL1	13	ANP LIGHTING	BVA2001 C046LD T4 40K XX MOUNTING FINISHES	BELLA VISTA	0.9	45.31
	SL2	17	ANP LIGHTING	BVA2001 C046LD T5 40K XX MOUNTING FINISHES *Twin Head Mounted @ 180 Degrees*	BELLA VISTA	0.9	90.9
	SL3	8	Lithonia Lighting	RSX1 LED P3 30K R4 VOLTAGE MOUNTING XX FINISH	RSX Area Fixture Size 1 P3 Lumen Package 3000K CCT Type R4 Distribution	0.9	109.44

STATISTICS

DESCRIPTION	SYMBOL	AVG.	MAX	MIN.	MAX/MIN	AVG/MIN
Calc Zone #1	+	0.9 fc	6.0 fc	0.0 fc	N/A	N/A
Pavement	+	1.9 fc	6.0 fc	0.1 fc	60.0:1	19.0:1

NOTES:

- REFLECTANCES ASSUMED:
GROUND: 20
- MOUNTING HEIGHTS:
SL1 / SL2: 16'-0" AFG
SL3: 20'-0" AFG
- TASK HEIGHT: 30" ABOVE FINISHED FLOOR
- CALCULATION POINT SPACING: 10'X10' OC

DISCLAIMER:

-THESE DRAWINGS ARE FOR CONCEPTUAL PURPOSES ONLY AND ARE NOT INTENDED FOR CONSTRUCTION. VALUES REPRESENTED ARE AN APPROXIMATION GENERATED FROM MANUFACTURERS PHOTOMETRIC IN-HOUSE OR INDEPENDANT LAB TEST WITH DATA SUPPLIED BY LAMP MANUFACTURERS.